

## Slickline Roller Sub

The Omega Slickline Roller Sub was designed to fill a need in the rolling systems market for a simple and reliable means of reducing toolstring friction in order to allow deeper penetration into deviated wellbores and also to enhance our slickline tractor and catapult operations.

The O.R.S. system features interchangeable hardened wheels that allow the fitment of the largest wheel size possible for a particular completion. The large diameter wheel has two positive benefits. It lifts the toolstring clear of any foreign bodies, scale or debris in the tubing preventing the tools between the rollers from "bellying out" on the tubing wall.

The large radius also allows easier passage over obstructions where smaller wheel sizes would encounter difficulty.

Each wheel features three bearings, two thrust and one double angular. The wheels are rigidly mounted on a threaded shaft that is double locked to the main body. The roller sub features four wheels per roller in a spiral, which guarantees two contact points with the tubing at any one time. In addition to reducing the effects of downhole friction on the toolstring, the Omega triple bearing system also acts to mitigate mechanical damage to tubing string that may be otherwise caused by repeated reciprocation of the wireline conveyed toolstring against the I.D. of the tubing string.


A roller sub for electric line operations is available which incorporates a monoconductor Type 44 cable protected by stainless steel tubing which is recessed into the sub body. Metal to metal seals on the tubing connections give a 10,000 p.s.i. rating for the sub.

# Technical Specifications

omega-intervention.com

## Slickline Roller Sub


Slickline Roller Sub						
Body O.D	1.375"	1.50"	1.75"	1.875"	2.5"	2.5"
Length	17.0"	20.0"	24.0"	24.0"	28.0"	34.0"
Wheel Diameter	1.6"	1.75" - 2.35"	2.0" - 3.0"	2.0" - 3.0"	2.7" - 4.3"	2.7" - 5.7"
Connections	All Connections Available	All Connections Available	All Connections Available	All Connections Available	All Connections Available	All Connections Available
Material	AISI 4140 30-36 Rc	AISI 4140 30-36 Rc	AISI 4140 30-36 Rc	AISI 4140 30-36 Rc	AISI 4140 30-36 Rc	AISI 4140 30-36 Rc
Weight	5.5 lbs	8.4lbs	10.3 lbs	11.5 lbs	21.6 lbs	37 lbs



# Features - Applications - Benefits

omega-intervention.com

## Slickline Roller Sub



### FEATURES

- Interchangeable hardened wheels.
- Thrust and angular bearings fitted throughout.
- Two contact points guaranteed with tubing at any one time.
- Extremely robust design.
- 360° Wheel coverage.

### APPLICATIONS

- Friction reduction in deviated well bores.
- Centralisation of downhole devices.
- Enhancement of tractor & catapult operations.

### BENEFITS

- Enhances jar impact.
- Enables use of wireline in high deviation wells.
- Provides "tool lift".
- Highly debris tolerant.

Omega Well Intervention Ltd, Omega House, Kirkhill Road, Kirkhill Industrial Estate, Dyce, Aberdeen, AB21 0GQ  
Tel: +44 (0)1224 772744, Email: info@omega-intervention.com  
www.omega-intervention.com

ED-012 R2.2

  
**Omega**  
Well Intervention